

## MP70 Single Direction Vibratory Plates



This plate proves that performance is valuable

With a powerful Wacker Neuson petrol engine, low weight, compact dimensions and low-maintenance design, the MP70 Vibratory Plate is ideal for the compaction of sand, crushed rock, granular materials and segmental brick paving.

- Compact design with centrally mounted, fully enclosed exciter for an even spread of compaction force over the whole base plate.
- Sturdy 4-stroke petrol engine with recoil starter is isolated from vibration by rubber dampers.
- Vibration isolated reversible handle with throttle control for ease of operation and reduced operator fatigue.
- Conveniently placed lifting handles, and a central lifting point for safe and easy handling.
- Low maintenance design.

MP70 Standard Package includes operator's manual and parts book.

Item No. 0630243



## Technical specifications

## Operating data

Operating weight (without fuel)	76 kg
Centrifugal force	15 kN
Base plate size (w × I)	460 x 610 mm
Advance travel max. (depending on soil)	30 m/min
Surface capacity max. (depending on soil)	830 m²/h
Engine / Motor	
Engine / Motor type	Air-cooled, single cylinder, 4-cycle gasoline engine
Engine / Motor manufacturer	Wacker Neuson
Engine / Motor	WN6
Displacement	179 cm <sup>3</sup>
Engine performance (max.)	4.2 kW
at rpm	3,600 rpm
Fuel consumption	1.27 l/h
Tank capacity	3.61

## Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2017 Wacker Neuson SE.